

SAFETY DATA SHEET

Naked Gun Spray Gun Paint Remover

Page: 1

Printed: 01/20/2015

Revision: 01/11/2015


Supersedes Revision: 07/24/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Naked Gun Spray Gun Paint Remover
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Web site address: www.wmbarr.com
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Intended Use: Removes both solvent and waterborne paints from hard to reach areas
Synonyms: ENGC11131

2. HAZARDS IDENTIFICATION

Flammable Gases, Category 1
Flammable Aerosols, Category 1
Gas Under Pressure, Compressed gas
Flammable Liquids, Category 2
Acute Toxicity: Inhalation, Category 4
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2
Germ Cell Mutagenicity, Category 1A
Carcinogenicity, Category 1B
Target Organ Systemic Toxicity (single exposure), Category 1
Aspiration Toxicity, Category 1
Simple Asphyxiant



GHS Signal Word: Danger

GHS Hazard Phrases: H220: Extremely flammable gas.
H229: Pressurized container: may burst if heated.
H280: Containers gas under pressure; may explode if heated.
H225: Highly flammable liquid and vapor.
H332: Harmful if inhaled.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H340: May cause genetic defects.
H350: May cause cancer.
H370: Causes damage to organs.
H304: May be fatal if swallowed and enters airways.

GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211: Do not spray on an open flame or any other ignition source.
P251: Do not pierce or burn, even after use.
P233: Keep container tightly closed.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P243: Take precautionary measures against static discharge.
P242: Use only non-sparking tools.
P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing gas/mist/vapours/spray.

Naked Gun Spray Gun Paint Remover

Printed: 01/20/2015

Revision: 01/11/2015

Supersedes Revision: 07/24/2012


P264: Wash hands thoroughly after handling.
 P362+364: Take off contaminated clothing and wash it before reuse.
 P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P281: Use personal protective equipment as required.
 P260: Do not breathe gas/mist/vapours/spray.
 P270: Do not eat, drink or smoke when using this product.
 P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381: Eliminate all ignition sources if safe to do so.
 P370+378: In case of fire, use dry chemical powder to extinguish.
 P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312: Call a POISON CENTER/doctor if you feel unwell.
 P302+352: IF ON SKIN: Wash with plenty of soap and water.
 P321: Specific treatment see directions on this label.
 P332+313: If skin irritation occurs, get medical advice/attention.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+313: If eye irritation persists, get medical advice/attention.
 P308+313: IF exposed or concerned: Get medical attention/advice.
 P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P331: Do NOT induce vomiting.

GHS Response Phrases:**GHS Storage and Disposal Phrases:**

P410+412: Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
 P410+403: Protect from sunlight and store in well-ventilated place.
 P403+235: Store in cool/well-ventilated place.
 P501: Dispose of contents/container according to local, state and federal regulations.
 P405: Store locked up.

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL		0
PPE		X

HMIS:**OSHA Regulatory Status:****Potential Health Effects (Acute and Chronic):****NFPA:**

This material is classified as hazardous under OSHA regulations.

INHALATION EFFECTS:

Vapor harmful. High concentrations of this material may lead to central nervous system effects, such as dizziness, headaches, nausea, drowsiness, paralysis, loss of consciousness, and even death. May cause watering and irritation of the eyes, nose, throat, and lungs. May cause irritation of the respiratory tract. Other effects may include nasal discharge, hoarseness, coughing, chest pain, and breathing difficulty.

Repeated or prolonged exposure to solvents may cause liver and kidney damage.

Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

SKIN EFFECTS:

Repeated or prolonged contact with the skin can result in defatting and drying of the skin which may result in skin irritation and dermatitis. Symptoms may include redness, burning, drying, cracking of the skin, and burning of the skin. Skin contact may aggravate

Naked Gun Spray Gun Paint Remover

Printed: 01/20/2015

Revision: 01/11/2015

Supersedes Revision: 07/24/2012

an existing dermatitis condition. May be absorbed through the skin.

EYE CONTACT EFFECTS:

Contact with the eyes may cause moderate to severe irritation. May cause slight to moderate corneal injury. Effects may include discomfort, pain, tearing, stinging, watering of the eyes, redness, and/or change of vision. Vapors may cause eye irritation, seen as mild discomfort and redness.

INGESTION EFFECTS:

Danger! Poison. Harmful if swallowed. Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death. Irritating to the mouth, throat, and stomach.

Medical Conditions Generally Aggravated By Exposure: Preexisting disorders and conditions of the following organs, or organ systems, may be aggravated by exposure to this material: skin, lungs, liver, kidney, central nervous system, pancreas, heart, chronic lung disease, coronary artery diseases, or anemias.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-64-1	Acetone {2-Propanone}	58.0 %
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	17.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	14.0 %
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	< 9.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	5.0 %
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	5.0 %
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	4.0 %
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	<=2.7 %
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	<=1.75 %
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	<=1.0 %
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	<=0.1 %

Additional Chemical Information The concentration range values for the liquid ingredients do not reflect the dilution of the propellant in the container. The concentration values are for the liquid concentrate only.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:
Remove contaminated clothing. Immediately wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists.

Eyes:
Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

Inhalation:
Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:
If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure:

See Potential Health Effects.

Note to Physician:

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

5. FIRE FIGHTING MEASURES

Flash Pt: Level 3 Aerosol
No data.

Explosive Limits: LEL: 1.8 % UEL: 12.8 %

Autoignition Pt: No data.

Suitable Extinguishing Media: Dry chemical, CO2, alcohol-resistant foam or water spray.

Unsuitable Extinguishing Media: None known.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.
Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas.

Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.
Stay away from heads of containers that have been exposed to intense heat or flame.
Containers can build up pressure if exposed to heat (fire).

Flammable Properties and Hazards: EXTREMELY FLAMMABLE.

Flashpoint of liquid concentrate: ~10 F (SCC)

Flashpoint of propellant: -142.5 F (closed cup)

Flammability Classification:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.

Small Spills: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills: dike far ahead of spill for later disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Danger! Contents under pressure. Do not puncture or incinerate. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Keep away from sources of ignition. Ground and bond containers when transferring material.

Precautions To Be Taken in Storing: Keep container closed when not in use. Do not store in direct sunlight. Store in a tightly closed container. Store in cool, dry area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No data.	No data.	No data.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	No data.
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	No data.	No data.	No data.
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm	No data.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
95-63-6	1,2,4-Trimethylbenzene	No data.	No data.	No data.

Naked Gun Spray Gun Paint Remover

Printed: 01/20/2015

Revision: 01/11/2015

Supersedes Revision: 07/24/2012

	{Pseudocumene}			
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	No data.	No data.	No data.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	PEL: 50 ppm	TLV: 50 ppm	No data.

Respiratory Equipment (Specify Type): A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

If the work area is not properly ventilated to keep airborne levels below their exposure limits, you must use a properly fitted and maintained NIOSH approved respirator for organic vapors. A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.

Protective Gloves: Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Other glove materials such as nitrile may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing: Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.

Engineering Controls (Ventilation etc.): Use only with adequate ventilation to prevent the buildup of vapors. Do not use in areas where vapors can accumulate and concentrate. Whenever possible, use outdoors in an open air area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area away from the individual. If strong odor is noticed or you experience slight dizziness, headache, nausea, or other signs of inhalation exposure, STOP. The ventilation is inadequate. Leave the area immediately.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Work/Hygienic/Maintenance Practices: A source of clean water should be available in the work area when handling this product. Wash hands thoroughly after use and before eating, drinking, or smoking. Do not eat, drink, or smoke in the work area. Discard any clothing or other protective equipment that cannot be decontaminated.

SAFETY DATA SHEET
Naked Gun Spray Gun Paint Remover

Page: 7
Printed: 01/20/2015
Revision: 01/11/2015
Supersedes Revision: 07/24/2012

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [X] Gas [X] Liquid [] Solid
Appearance and Odor: Liquid, mobile, free and clear.
Melting Point: No data.
Boiling Point: No data.
Autoignition Pt: No data.
Flash Pt: No data.
Explosive Limits: LEL: 1.8 % UEL: 12.8 %
Specific Gravity (Water = 1): 0.808
Density: 6.755 LB/GL
Vapor Pressure (vs. Air or mm Hg): 29.45 MM HG at 68.0 F
Vapor Density (vs. Air = 1): > 1
Evaporation Rate: > 1
Solubility in Water: partially
Percent Volatile: 100.0 %
VOC / Volume: < 50.0000 % WT

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: No data available.
Incompatibility - Materials To Avoid: Chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol. Strong oxidizers and acids. Nitric acid, sulfuric acid. Avoid contact with reactive metals, such as aluminum and magnesium.
Hazardous Decomposition Or Byproducts: Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: No data available.

11. TOXICOLOGICAL INFORMATION

- Toxicological Information:** Product has not been tested as a whole.
- CAS# 67-64-1:
Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.
Result:
Behavioral: Change in motor activity (specific assay).
Behavioral: Alteration of classical conditioning.
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946
- CAS# 67-56-1:
Mutagenicity:, Mutation test: DNA damage., Oral, Rat, 10.00 UMOL/KG.
Result:
Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.
Tumorigenic:Tumors at site of application.
- Environmental Mutagenesis., For publisher information, see EMMUEG, New York, NY, Vol/p/yr: 4,317, 1982
- CAS# 1330-20-7:
Standard Draize Test, Skin, Species: Rabbit, 100.0 %, Moderate.
Result:
Specific Developmental Abnormalities: Craniofacial (including nose and tongue).
- AMA Archives of Industrial Health., For publisher information, see AEHLAU, Chicago, IL, Vol/p/yr: 14,387, 1956
- Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.
Result:
Behavioral: General anesthetic.
Behavioral: Somnolence (general depressed activity).
Behavioral: Irritability.
- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972
- CAS# 111-76-2:
Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.
Result:
Behavioral: Ataxia.
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.
- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983
- Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
Result:
Effects on Newborn: Apgar score (human only).
Effects on Newborn: Other neonatal measures or effects.
Effects on Newborn: Drug dependency.
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

SAFETY DATA SHEET
Naked Gun Spray Gun Paint Remover

CAS# 78-93-3:
 Standard Draize Test, Eyes, Human, 350.0 PPM.
 Result:
 Behavioral: Anticonvulsant.
 - Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943

CAS# 100-41-4:
 Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.
 Result:
 Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).
 Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).
 Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).
 - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Carcinogenicity/Other Information:

IARC 3: Not Classifiable as to Carcinogenicity in Humans.
 IARC 2B - Possibly Carcinogenic to Humans
 ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
 ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	n.a.	n.a.	n.a.	n.a.
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	n.a.	n.a.	n.a.	n.a.
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	n.a.	n.a.	n.a.	n.a.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	n.a.	2B	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: Product has not been tested as a whole.

SAFETY DATA SHEET

Naked Gun Spray Gun Paint Remover

Page: 10
Printed: 01/20/2015
Revision: 01/11/2015
Supersedes Revision: 07/24/2012

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Aerosols, flammable
DOT Hazard Class: 2.1 FLAMMABLE GAS
UN/NA Number: UN1950



Additional Transport Information: The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

This material meets the EPA Yes No Acute (immediate) Health Hazard
'Hazard Categories' defined Yes No Chronic (delayed) Health Hazard
for SARA Title III Sections Yes No Fire Hazard
311/312 as indicated: Yes No Sudden Release of Pressure Hazard
 Yes No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 8A PAIR, 8D TERM; CA PROP.65: No
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes

SAFETY DATA SHEET
Naked Gun Spray Gun Paint Remover

Page: 11

Printed: 01/20/2015

Revision: 01/11/2015

Supersedes Revision: 07/24/2012

16. OTHER INFORMATION

Revision Date: 01/11/2015

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.