

DESCRIPTION

Guide Coat is an aerosol coating that helps detect low spots, sand scratches or other minor imperfections prior to sanding primer.

FEATURES

- Quick drying
- Improves production
- Won't clog sandpaper
- Helps create a perfect repair

SUITABLE SUBSTRATES

- Primer

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
38203	Guide Coat	Black	Aerosol

MIR: Category ABP < 1.55

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION

PREPARATION:

Complete repair per manufacturer's instructions.

MIXING:

Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).

APPLICATION:

Apply a light "mist" coat over the area. Sand until Guide Coat can no longer be seen.



Check local VOC regulations to ensure compliance of all products in your area.

Note:

If clogging develops, remove spray button with a twisting motion and clean with **XXX Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE:

Guide Coat should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Guide Coat** is 3 years when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:
77743	XXX Gun Cleaner	Aerosol

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.