



UP0670, UP699 LIQUID GOLD Pourable Glazing Putty

Description	LIQUID GOLD is a two component polyester filler paste used for the filling of holes and imperfections in most substrates. The LIQUID GOLD formulation uses sophisticated lightweight technology to produce excellent filling properties combined with smooth application and easy sanding. If so desired, LIQUID GOLD may be mixed with U-POL's FLYWEIGHT GOLD to adjust the product's viscosity. It has been designed with the most challenging professional applications in mind.
Health and Safety Statement	<u>FOR PROFESSIONAL USE ONLY</u> . Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM . U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.
Surface preparation & instructions for use	LIQUID GOLD polyester filler can be used on the following surfaces:- <ul style="list-style-type: none">• Bare metal – e.g. Steel, degrease and abrade with P80 paper.• Original paint surfaces (with the exception of thermoplastic acrylics) degrease and abrade with P180 grit paper.• GRP degrease and abrade with P80 grit paper.
Mixing Ratio	100 parts by weight LIQUID GOLD polyester filler, 2 parts by weight U-POL hardener for polyester filler. The exact mixing ratio is not critical, although over or under catalyzation may affect the gel time. Do not greatly over catalyze the paste as this will not significantly speed up the gel time and could lead to bleed through and bleaching problems when over-painting later. Staining may also occur where too little hardener is used.
Pot life	Once mixed, 4-5 mins. at 68°F with 2% hardener.
Tools	Mixing board, filler knife, plastic or rubber spatula.
Drying Time	Sandable after 20 mins. at 68°F. IMPORTANT – This filler is very easy to sand and therefore recommend that nothing coarser or lower than P80 paper is used.
Over painting	LIQUID GOLD polyester filler can be over-painted with most paint systems including 2K.
Product Code	UP0670 615ml Squeezable Bottle UP699 550ml Filler Bag

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064
Tel: (800) 340 7824; Fax: (800) 787 5150
Email: sales-us@u-pol.com Website: www.u-pol.com

Issue 9/2012