# TURBO CUTTIME RELEASE COMPOUND

WIZARDS DATA SHEET • COMPLETE PRODUCT INFORMATION



# **AUTOMOTIVE**

**32 fl. oz. - 946 ml**Part No. 11044
6/case
Net Wt. 17 lbs.

1 Gallon - 3.785 liters Part No. 11043 4/case Net Wt. 44 lbs.

# **DETAILING • CLEANING • PROTECTION**

### **DESCRIPTION:**

WIZARDS® TURBO CUT™ is an aggressive compound designed for machine or hand application. It is recommended for removing 1200 grit or finer sand scratches (or similar sized finish imperfections) from new or aged paint finishes – factory, custom - foreign or domestic.

# **BENEFITS:**

TURBO CUT™ buffing compound will quickly and easily remove 1200 and finer grit sand scratches from fresh or aged finishes. This unique formula features an exclusive time release abrasive which starts out aggressively and, as you work, becomes less aggressive quickly creating a smoother finish.

TURBO CUT<sup>™</sup> is fast acting to restore dead paint, fiberglass and marine gelcoat, while remaining user friendly. The compound provides an incredible gloss without the headaches of excess dust, slinging, sticking, staining or gummed up and blocked pads. It levels to a smooth 4000 grit, non-oily, non-greasy finish.

TURBO CUT™ will clean up fast and easy

by wiping with a towel or rinsing with water.






WizardsProducts.com

### **FEATURES:**

- VOC compliant. TURBO CUT<sup>\*</sup> contains no wax, silicone or crystalline silica.
- Removes 1200 & 1500 grit sand scratches & similar size paint defects.
- · Cuts smoothly and quickly.
- Will not stick, sling or load up pads.
- Water-based for easy clean-up without staining.
- Will not stain or etch painted surfaces.
- Leaves no oily residue or greasy film.





## **HOW TO USE:**

Make sure painted surfaces are clean, cool and dry. Shake product and apply a generous amount to one spot, not ribbons or specks. Place pad directly on top of compound, running buffer speed at 1000-2200 RPM. Move slowly, avoiding fast back and forth motions. Work a 2 to 4 square foot section at a time. Apply adequate pressure to remove scratches and speed up the process.

WOOL PAD #11203. For the fastest cut use our FAST CUT WOOL PAD #11201. Follow up with #11040 FINISH CUT\* and the WHITE FOAM CUTTING PAD #11310. Remove residue to inspect surface using WIPE DOWN\* #01220. For maximum protection use SHINE MASTER\* Polish and Breathable\* Sealant #11033 with the BLUE ULTRA FINISHING PAD #11314 or by hand.